



MODEL 34B



Pulse Oximeter with Alarms, Memory, Printer option, USB & Infrared Ports

Applications

Physician's Office, Emergency Care, Hospitals, Clinics, Diagnostic Centers, Home Health Care, Sleep Screening

Key Features

- Hand held pulse oximeter that is ideal for most continuous monitoring applications.
- Bright LED displays indicate oxygen saturation and heart rate from any angle and in most lighting conditions
- Bar graph displays for Pulse Amplitude and Perfusion Quality indication
- Online/Remote monitoring ability through USB port.
- Audible Pulse tone varies in pitch with rise & fall of Oxygen Saturation
- Audio and Visual alarms for saturation and pulse rate
- 136 hours patient data storage facility
- Plethysmograph display on computer using optional software.
- Ability to output/print trend data via USB & infrared ports.
- Simple keypad layout makes units user friendly
 - Unique averaging sequencing technique updates values and provides faster response time
 - Continuous battery condition indicator
 - Fits easily into lab coat pocket

Specifications

Pulse Oximetry and Heart Rate

Display	Two 3 Digit, 7-Segment LED for %SpO ₂ & Pulse Rate Two 10-Segment LED Bar graph for Pulse Amplitude (PA) and Perfusion Quality (PQ) indication
Resolution	SpO ₂ 1% Pulse 1 BPM
Range	SpO ₂ 0 – 100% Pulse 25 – 250 BPM
Reading Accuracy	SpO ₂ 100 – 70%, ± 2% Less than 70%, Unspecified Pulse 25 – 250 BPM, ± 2 BPM or 2% whichever is greater
Alarm	High SpO ₂ 87 – 100% Low SpO ₂ 85 – 98% High Pulse 26 – 250 BPM Low Pulse 24 – 248 BPM

Sensors

Mediaid Pulse Oximetry sensors with Compushield® Connector

Size & Weight

Size	5.5 in x 3 in x 1.1 in (L x W x H) 14 cm x 7.6 cm x 2.7 cm (L x W x H)
Weight	202 gm, 7.12 oz (without sensor)

Electrical Ratings

Battery Type	AAA Battery
Battery Run Time	21 hours of Operation (in Sleep mode with low speaker volume)

Environmental conditions

(Acceptable conditions for operating, storage and transport)

Atmospheric Pressure	770 to 282 mmHg 1026 to 377 hPa
Humidity	5 to 95% (non condensing)
Operating Temp	0 to 40 °C
Storage / Transport Temp	-30 to 65°C



PRINTER OPTION FOR MODEL 34B



Key Features

- High speed printing of patient report
- Infrared communication with Model 34B
- Low power consumption
- Battery of DC mode options
- Single Charge battery life up to 2000 reports of 5cm each
- Audio & Visual Indication of power ON, charging completion & busy indication
- Operation controlled with single button switch
- Platen open Detection
- Paper out Detection

The Model 34B has memory to retain oxygen saturation and pulse rate data, and can operate in three different modes to best suit your needs:

- The Model 34B can retain up to 136 hours of information for a single patient, making the device ideally suited for treadmill or other long tests.
- The Model 34B can be used in walk around tests, storing more than 7200 data for up to 20 consecutive patients, tagging each reading with a patient number, time and date
- The Model 34B can also be used for sleep screening where data can be stored every 5 seconds for up to 18 hours.

Specifications

Print Data	
Print Method	Line Thermal Dot Printing
Resolution	0.125 mm dots (8 dots/mm)
Effective Printing Area:	
	48 mm
Paper Feeding Pitch	0.125 mm
Printing Speed	18 lines per second (24 and also 42 characters in 1 line)
Interface Conformity	IR @ 9600 bps
Thermal Paper	
Paper Thickness	60-72 uM
Paper Width	57.5 mm
Recommended Paper	TF60KS-E Nippon Paper PDI50R Oji Paper
Size & Weight	
Size	5.1 in x 3.2 in x 1.6 in (L x W x H) 13 cm x 8.1 cm x 4 cm (L x W x H)
Weight	240 gm, 8.46oz (without paper roll)
Electrical Ratings	
Charging Voltage	Single + 9V supply
Consumption	Less than 1mA in standby mode and few uA in deep sleep mode
Environmental Conditions	
Operating Temp	0 to 50 °C
Relative Humidity	5 to 90% (non condensing)

1010-60023-001

17517 Fabrica Way Suite H
Cerritos, CA 90703 USA
(Tel) 714-367-2848 (Fax) 714-367-2852
www.mediaidinc.com info@mediaidinc.com